

Material Safety Data Sheet

Product Name: 4 Seasons™ Liquid Pothole Filler- Winterized & Regular Formula
Product Code: PART 2- AGGREGATE

Section I: Manufacturer Identification

Manufacturer's Name: Integrity Marketing Group Inc.
Address: 777 Industrial Park Dr. Shelby, MI 49455
Emergency Phone: (888) 755-0997
Information Phone: (231) 861-7126
Name of Preparer: Steven Arnold
Date Revised: 7/1/08

Section II: Hazardous Ingredients/SARA III Information

HAZARDOUS COMPONENTS	Occupational Exposure Limits			Vapor Pressure		Weight	
	CAS NO.	OSHA PEL	ACGH TLV	OTHER mmHG	TEMP	PERCENT	
GYP SUM	7778-18-9	15mg/m3	10mg/m3	N/A	N/A	N/A	N/A
PUMICE	1332-09-8	15mg/m3	10mg/m3	N/A	N/A	N/A	N/A
PROPRIETARY BLEND FILLER *	N/A	N/A	10mg/m3	N/A	N/A	N/A	N/A

*Non- hazardous, non flammable, proprietary as written in 49CFR Rules for such products

Section III: Physical/Chemical Characteristics

Boiling Range: N/A
Vapor Pressure: N/A
Vapor Density (Air=1): N/A
Solubility in Water: 0.2%
Appearance & Odor: OFF-WHITE, TAN, GRAY, BLACK GRANULES, LOW ODOR

Specific Gravity (H₂O=1): 2.7
Melting Point: (decomposes) 1450° C
Evaporation Rate: N/A
Harding Time: 15-20 minutes

Section IV: Fire and Explosion Hazard Data

Flash Pont: NONE
Extinguishing Media: NOT COMBUSTABLE
Unusual fire and explosion hazards: NONE

Section V: Reactivity Data

Stability: STABLE
Hazardous Decomposition or byproducts: Above 1450°C- SO₂ and CaO
Hazardous Polymerization: Will not occur

Incompatibility: NONE KNOWN

Section VI: Health Hazard Data

Routes of Entry: INHALATION
Health Hazards (Acute):
Inhalation: Nuisance dust
Skin: Irritation, prolonged exposure while hardening can cause heat build up and mild burns
Eyes: May cause irritation
Ingestion: Stomach irritation, nausea, vomiting. May cause blockage
Chronic: None
Carcinogenicity:
NTP? NONE **IARC Monographs?** NONE **OSHA Regulated?** NONE

Signs & Symptoms of Exposure: Irritated eyes from dust, difficulty breathing, irritated skin
Medical Conditions Aggravated by Exposure: Respiratory system, irritated eyes or open wounds

EMERGENCY & FIRST AID PROCEDURES:

Eyes: Flush with running water
Inhalation: Move to fresh air
Skin: Wash with soap and water. Contact physician if irritation persists

Section VII: Precautions for Safe Handling and Use

In case material is released or spilled: Sweep up. Avoid creating excessive dust. Slurry may plug drains.

Waste Disposal Method:

Waste can be reused if clean. Otherwise, waste should be disposed of according to prevailing regulations.

Precautions to be taken in handling and storing:

Dew point conditions or other conditions causing presence of liquid/water during storage will cause gypsum to harden.

Section IX: Disclaimer

Disclaimer:

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding accuracy of these data or the results to be obtained from the use thereof. The Manufacturer assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by this material.