

4 Seasons™ Pourable Pothole Filler

DESCRIPTION 4 Seasons™ is a liquid, rubberized, pourable filler, used to fill cracks, potholes & irregularities in asphalt, & concrete pavement. A two part blend of liquid asphalt polymers, and aggregate, 4 Seasons™ liquid pothole filler sets up quickly, in as little as 40 minutes, enabling repairs to be drivable in 40 minutes to an hour.

USED BY • DOT's • Asphalt/ Sealcoat Co. • Construction Co. • Cement Contractors • Maintenance Crews • Business Owners • Homeowners • Do-It-Yourselfers

EASY TO USE

Remove contents from pail/liner (**Additional Activator Bag, Aggregate Bag, Liquid Bladder**).

Shake **Liquid Bladder** gently before pouring contents into pail.

Shake **Aggregate Bag**, *(Add **Activator Bag**: ½ bag, 50-60° F; entire bag, below 50°F). Shake to distribute activator, then pour contents **Into Liquid** in pail. **Do not use** additional activator for temps +60°F.

Mix with disposable stir stick **40 seconds, OR until thoroughly mixed**. **DO NOT USE POWER MIXER!**

IMMEDIATELY POUR FILLER into hole, using flat side of stir stick to assist product flow.

Allow traffic to resume after **30-40 MINUTES**.

Dispose of/recycle packaging according to local requirements.

SUGGESTED USES • Roads, Highways • Expansion Joints • Parking Lots • Bridge Decks • Sidewalks • Bike Paths • Tennis Courts • Warehouse/Garage Floors • Sewer Grates • Manhole Covers

BENEFITS • Non-Hazardous • Non-Toxic • Self Priming • Self Leveling • Environmentally Safe • Used In Both Warm & Cold Climates

PACKAGING Environmentally friendly, 4 Seasons™ is available in recyclable cardboard packaging! With a convenient, disposable plastic liner, and resealable, disposable liquid bladder, it not only is easy to use, but easy to dispose of! No more rigid pails that don't decompose in landfills. Each #5 4 Seasons™ kit fills approx. 900 cu. in. Mix only the product amount required for your repair!

STORAGE Do not allow to freeze before use. Store above 40 degrees F. Do not allow contents to come in contact with each other until you are ready to mix and pour filler material, as chemical reaction for set up will occur. Keep out of reach of children.

CAUTIONS Rubber gloves and safety glasses recommended because liquid may splatter. Do not take internally. If ingestion occurs, do not induce vomiting. Call physician. Do not open or mix until ready to use. Clean up: citrus cleaner; mineral spirits if needed. Avoid prolonged inhalation of dust from aggregate. Dust mask may be needed in heavy use areas.

TECH SUPPORT Toll Free Tech Support is just a phone call away! For help with specific pothole or pavement repairs, **call Toll Free 1-888-755-0997** (8 AM-5 PM EST, Mon-Fri)

Distributed by: PTI Pavement Repair Products
Technical Support 281-778-3223

Visit us on the web at:
www.pavepatch.com

4 Seasons™ Pourable Pothole Filler

Application Procedure for Potholes



First step in filling any pothole is to estimate the size, and how much material is needed to fill the pothole.

The entire contents of liquid and aggregate, when mixed as instructed, will yield 900 cu inches of filler. Lesser amounts may be portioned out for smaller repair needs.

Use direct ratios: i.e. 50% liquid to 50% aggregate. Use a smaller disposable pail if partial mixing is required. Pail will not be reusable.

Re-cap unused liquid and close aggregate bag for future use.

If more product is needed to repair area, repeat application procedure. 4 Seasons will adhere to itself.

Prepare the hole for the fill material. Sweep out loose debris, being careful to remove sand and gravel that is at the edge where product sealing must occur.

Larger pieces of concrete or asphalt may be placed in bottom of hole to help fill space and reduce product amount.

Sand is not recommended to fill hole, as product needs appropriate surface to adhere to.

Clean visible grease and oil from surface.

Next, prepare fill material according to instructions on box; pouring product into prepared hole; leveling product with stir stick or cement trowel if needed; assuring product is in good contact with the edge of the pothole.

If repair edge is open, with no adjacent pavement to hold repair material, form boards must be made from wood or similar substance wrapped in plastic to release the form once product is cured.

Place wrapped form boards on edge of repair area and secure with stakes on outside of board.

Use cement trowel to level poured product to boards and surrounding surfaces. Remove form boards immediately after 4 Seasons begins to set up.

Let the material set up and become firm before resuming traffic, usually between 40-60 minutes. Hotter climates will produce shorter working times. Colder or winter climates cause product to set up more slowly, although winter weather should not hamper the use or effectiveness of 4 Seasons.

Distributed by: PTI Pavement Repair Products
Technical Support 281-778-3223

Visit us on the web at:
www.pavepatch.com

4 Seasons™ Pourable Pothole Filler

Application Procedure for Cracks



4 Seasons pothole filler can be used for cracks ranging from 1/2" on up.

Estimate material needed and assess the situation for proper fill of area.

Remove sand and debris from repair area. Clean visible grease and oil from surface.

If the crack is narrow you will need to reduce the amount of aggregate that you add to the liquid in order to achieve a product thin enough to pour and penetrate deep into the crack.

In this situation, mixing 4 Seasons in a smaller container like a 5 quart pail will work just fine. Start by pouring 2" of liquid into pail.

Mix in slowly, a small amount of aggregate to achieve a pour able consistency. Pour into crack and level off, ensuring that good contact between the edge of the crack and the 4 Seasons product has been made.

Any remaining liquid and aggregate must be used in like manner.

Product initially comes proportioned for successful pothole filling.

Using partial amounts, as in dealing with larger cracks, causes the ratios to be unbalanced. It will not be successful for pothole filling.

Distributed by: PTI Pavement Repair Products
Technical Support 281-778-3223

Visit us on the web at:
www.pavepatch.com

4 Seasons™ Pourable Pothole Filler

HIGH PERFORMANCE GUARANTEE

NewLife Surface Solutions, LLC

Guarantees that NLSS Pothole Filler 4Seasons™ will perform as follows or full replacement:

1. WILL STAY IN PLACE FOR THE LIFE OF THE SURROUNDING PAVEMENT WHEN APPLIED ACCORDING TO WRITTEN INSTRUCTION.
2. WILL REMAIN WORKABLE FOR USE IN SUBFREEZING TEMPERATURE. CONSULT STORAGE INFORMATION.
3. WILL PERFORM IN EXTREME WEATHER CONDITIONS.
4. REQUIRES NO PRIMING.
5. WILL NOT BLEED THROUGH OVERLAPS.
6. REQUIRES LITTLE PLACEMENT.
7. IS SELF – LEVELING.
8. NON – TRACKING AFTER 30 MINUTES.

Customer satisfaction guaranteed!

Distributed by: PTI Pavement Repair Products
Technical Support 281-778-3223

Visit us on the web at:
www.pavepatch.com